



L20/480 HYGIENIC GRP DOOR SETS

Lami SV Type Non Fire Rated Double Action Door Sets

Manufacturer and supplier:

Lami Doors UK Ltd., Station House, Stamford New Road, Altrincham, Cheshire, WA14 1EP.

Tel. +44 (0)161 924 2217, Fax +44 (0)161 924 2218,

lamidoors@lamidoors.com

www.lamidoors.com

Door leaf: 7mm thick pressure moulded Glass Reinforced Polyester door leaf. Thickness decreases from 7mm to 5mm towards the leading edge. 40mm thick moulded section along the hinge edge to provide added rigidity. Moisture absorption 0 %

Reference: **Lami Type SV** non fire rated double action door set

Sizes: [See list of manufacturer's standard sizes](#)

Leaf colour: [Selection from Lami standard colour range](#) or colour from RAL/BS colour charts

Frame: Adjustable aluminium wrap around frame to suit to wall thickness for 68-256mm

Frame colour: RAL 9016 white powder coated or natural anodized aluminium

Hinges: Lami No. 2519 double swing hinges with hold open or non-hold open facility

Seal: Integral silicon seal in the frame

Bottom seal: Single silicon seal fitted to the bottom of door leaf

Glazing: Single glazed 200x500x3mm acrylic with grey rubber. Optional for DDA and BS8300 compliance

Protection: 5mm thick smooth polyethylene in standard grey colour RAL 7035, 1000mm high both sides

Fixing: Fix direct to structure with stainless steel screws

Optional: Grey 5mm thick polyethylene door bumper